

Product Data Sheet

PI-5945500 – Tamp Applicator Type 1200L-220H



Example: Hermes 4 with tamp applicator type 1200L-220H



Technical Description:

The tamp applicator type 1200 as module for thermal transfer printer Hermes 4 and Hermes 5 enables the fully-automatic labeling in real time applications. The products must be in resting position. Usually, the application is started by an external signal.

In the basic position the label is taken directly from the printer by an adapted tamp pad with the help of supporting air jet streaming and kept by vacuum. This process is detected by a vacuum sensor.

After having taken the label the tamp pad moves towards the product by the help of a pneumatic cylinder. Final position is detected by another sensor.

Communication between printer and applicator is effected by a cab standardized SPI interface. Link to a host process is carried out by a PLC interface at the applicator.

Technical Specifications:

Label width in mm:	8-112
Minimum width of liner in mm:	25
Label height in mm:	5-20
Applicator stroke in mm:	220
Appl. stroke under bottom line of printer in mm:	165
Immersion depth of tamp (size F) in mm:	20
Adjustable force to apply	Yes
Controlled vacuum circuit	Yes
Adjustable supporting air jet streaming	yes
Direction of application referring to printer:	downwards
Max. number of labels / minute:	30
Tamp pad size depending on label:	yes
Adjustable speed of applicator stroke:	yes
Distance product / applicator:	variable
Requirements regarding product surface:	flat / curved in limits
Motion of product:	in resting position
Compressed air supply (dry/oiled) in bar:	5-6
PLC interface for integration:	yes
Designed to be assembled to Hermes, type:	Hermes 4 /Hermes 5

Options:

- Right edition for Hermes 4/5 R
- Applicator stroke between 100-400 mm
- Light barrier to start application
- Test box to simulate complete print and apply cycle

Technical Data:

Designation: Type 1200L-220H
Article no.: 5945500
Power supply: internal
Power consumption: max. 50 Watt
Weight in kg: 5-6
Total weight of packaging in kg: 8